



PRODUCT DESCRIPTION

REXCO 18 SPECIALIST CONTACT CLEANER is a specialist product for cleaning electronic components, motherboards, electrical panels from dust and leaving no residue.

REXCO 18 SPECIALIST CONTACT CLEANER products use materials that dry very quickly with cleaning effectiveness that is precise enough so that it will not cause electrical short circuit.

REXCO 18 SPECIALIST CONTACT CLEANER is a product specifically designed to clean electrical equipment and electronic removes oil, dirt, residue and condensation from sensitive electronic and electrical equipment. **REXCO 18 SPECIALIST CONTACT CLEANER** is ideal for use on computer components, circuit breakers, circuits, contacts, flux removal, sockets, lighting, plastics, nylon, plugs, relay switches, PVC, precision instruments and electrical panels.

PRODUCTS



220 ML

500 ML

PRODUCT APPLICATIONS

- Electrical Panels
- Circuit Boards
- Dynamo Reels
- Electric Car Panels
- Computers
- Telecommunication Panels

ADVANTAGES & FEATURES

- **REXCO 18 SPECIALIST CONTACT CLEANER** Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- **REXCO 18 SPECIALIST CONTACT CLEANER** Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- Cleans electronic components.
- Easy to evaporate & does not leave residue.
- Does not conduct electricity and non corrosive.
- Easy to use & dries quickly.
- Removes oil, grease & dust.
- Acetone free.
- Chlorine free.

DIRECTIONS FOR USE

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application.
- Hold the can and apply from a distance of 15-20 cm. Apply the components thoroughly and paying particular attention to the seized contact areas.
- In same severe cases, apply **REXCO 18 Specialist Contact Cleaner** for second time after several minutes may be beneficial.
- Use 360° valve, can be sprayed in any direction.
- Save to use on fabric, plastic, paint, and other finishes.
- **CAUTIONS** : Pressurized container, protect from sunlight, do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Do not breathe spray. Avoid contact with the skin.
- **KEEP OUT OF REACH OF CHILDREN.** Contains distillates (petroleum), hydro treated light.

TECHNICAL DATA TEST

PARAMETERS	UNITS	TYPICAL DATA	METHODS
Appearance	-	Light Transparent	Visual
Odour	-	Solvent odour	-
Solubility in Water	-	Not Soluble	-
Vapour Pressure at 42 °C	Mm Hg	400	ASTM D323-20
Specific Gravity at 27°C	-	0.6500	ASTM D4052-11
Color ASTM	-	L 0.5	ASTM D1500-12
Kinematic Viscosity at 27°C	cSt	N/A	ASTM D445-14
Flash Point COC	°C	-7 °	ASTM D92-12b
Boiling Point	°C	60	ASTM D1120-94 (Reapproved 2004)
PH	-	N/A	-