



PRODUCT DESCRIPTION

REXCO 81 CARB & INJECTOR CLEANER is a REXCO product that has a function to clean the combustion system in motor vehicles, both cars and motorbikes. This product is very effective in cleaning impurities in the combustion system quickly and easily and does not have a corrosive impact on the surface of the combustion system.

REXCO 81 CARB & INJECTOR CLEANER Helps overcome hard starting, rough idling, stalling, and high exhaust emissions with quickly removes deposits from the inside and outside of the carburetor to improve engine performance and fuel economy. Cleans dirt, carbon, varnish and gum on the carburetor and injector system. carburetor and injector system. Prevents carbon build-up on indirect fuel injectors, carburetors, intake valves and ports.

PRODUCTS



300 ML

500 ML

ADVANTAGES & FEATURES

- ☑ **REXCO 81 CARB & INJECTOR CLEANER** Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- ☑ **REXCO 81 CARB & INJECTOR CLEANER** Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- ☑ Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- ☑ Maintain performance and fuel economy.
- ☑ Cleans dirt, carbon, varnish and gum.
- ☑ Freeing the automatic choke from jamming.
- ☑ It can also be used to clean the carburetors linkage mechanism so that it works smoothly.
- ☑ Maximizes performance and reduces emissions.
- ☑ Leaves no residue.
- ☑ Equipped with anti-corrosion.
- ☑ Quick penetration.
- ☑ Contains 100% high-energy solvent technology.
- ☑ Acetone free.
- ☑ Chlorine free.

PRODUCT APPLICATIONS

- Cleans Carburetor
- Cleans Injector
- Cleans Choke
- Cleans Valve
- Cleans Combustion Chamber

DIRECTIONS FOR USE

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application. Hold the can and apply from a distance of 15-20 cm. Apply the components thoroughly and paying particular attention to the seized contact areas.
- With the engine running and the engine speed is low, remove the air filter while spraying the REXCO 81 liquid into the combustion chamber, increase the engine speed slowly until sprayed liquid come up into the combustion chamber and clean the dirt from the fuel intake chamber to the engine combustion chamber.
- **CAUTIONS** : Flammable. Vapor Harmful. Use in well-ventilated area.
- Keep away from heat source, sparks (including those form electrical equipment) and flames. May cause eye and skin irritation. Do not breathe vapors. Do not swallow. **FIRST AID** : In case of eye and skin contact, wash with water for 15 minutes. If swallowed do not induce vomiting. If too much is breathed remove to fresh air. For severe overexposure get medical attention immediately.
- **KEEP OUT OF REACH OF CHILDREN.** Contains distillates (petroleum), hydro treated light.

TECHNICAL DATA TEST

PARAMETERS	UNITS	TYPICAL DATA	METHODS
Appearance & odour	-	Clear Transparent	Visual
Odour	-	Solvent odour	-
Solubility in water	-	Not Soluble	-
Specific Gravity at 27°C	-	0.8537	ASTM D4052-11
Color ASTM	-	L 0.5	ASTM D1500-12
Kinematic Viscosity at 27°C	cSt	0.802	ASTM D445-14
Flash Point COC	°C	<79	ASTM D92-12b
Boiling Point	°C	73.0	ASTM D1120-94 (Reapproved 2004)
PH	-	6.02	Potentiometric