



PRODUCT DESCRIPTION

REXCO 50 MULTIPURPOSE LUBRICANT is an excellent multi purpose lubricating product that provides rust resistance over a long period of time to improve equipment performance and protector of metal objects from the oxidation process which cause rust or corrosion. **REXCO 50 MULTIPURPOSE LUBRICANT** is able to lubricate metals that rubs against each other even under heavy load and heat, it will reduce the creaking sound and slow down the metal from wear out quickly.

REXCO 50 MULTIPURPOSE LUBRICANT has a strong penetrating power and works quickly to penetrate even the deepest layers, with a quick penetration **REXCO 50 MULTIPURPOSE LUBRICANT** is very effective for cleaning: stains, oil, grease, dust, asphalt that sticks to the surface (Metal, Aluminium, Chrome and painted metal objects does not damage the paint).

PRODUCTS



120 ML 220 ML 350 ML 500 ML 3,8 L

PRODUCT APPLICATIONS

- Industrial Machines
- Household
- Refinery Pipe
- Workshops
- Marine
- Hobbies
- Automotive Components

ADVANTAGES & FEATURES

- ☉ **REXCO 50 MULTIPURPOSE LUBRICANT** Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- ☑ **REXCO 50 MULTIPURPOSE LUBRICANT** Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- ISO Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- Loosens rusty parts.
- Protects from oxidation & corrosion.
- Removes moisture.
- Eliminates squeaks.
- Cleans & removes oil, asphalt & dust.
- High performance lubrication.
- Protects metal surfaces from rust for longer time.
- Chlorine free.

DIRECTIONS FOR USE

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application.
- Hold the can and apply from a distance of 15-20 cm. Apply the components thoroughly and paying particular attention to the seized contact areas.
- In same severe cases, apply **REXCO 50 Multipurpose Lubricant** for second time after several minutes may be beneficial.
- Use 360° valve, can be sprayed in any direction.
- Save to use on fabric, plastic, paint, and other finishes.
- **CAUTIONS** : Pressurized container, protect from sunlight, do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Do not breathe spray. Avoid contact with the skin.
- **KEEP OUT OF THE REACH OF CHILDREN.** Contains distillates (petroleum), hydro treated light.

TECHNICAL DATA TEST

PARAMETERS	UNITS	TYPICAL DATA	METHODS
Appearance	-	Yellow Transparent	Visual
Odour	-	Mild Smelling	-
Solubility In Water	-	Not Soluble	-
Specific Gravity At 27 °c	-	0.9578	Astm D4052-11
Color Astm	No. Astm	L 3.0	Astm D1500-12
Kinematic Viscosity At 27 °c	Cst	3.108	Astm D445-14
Boiling Point	°c	193	Astm D1120-11
PH	-	5.40	Potentiometric
Flash Point COC	°c	68	Astm D92-12